Open Cloud Connect

Cloud Services Architecture, SDN, NFV, and Management

Mehmet Toy, Ph.D Comcast January, 2016 CL ETSI NFV Meeting



Outline

- OCC Reference Architecture Fundamentals
- Cloud Service Actors
- Cloud Service Architectures: Interfaces and Connections
- Common Attributes of Cloud Services
- OCC vs ETSI NFV Architectures
- Mapping Between OCC and NFV Interfaces
- Cloud Services Management Architecture
- Open Cloud Project Test Bed
- What is Next?



OCC Reference Architecture Fundamentals

- •Cloud Services provided over a Cloud Service Connection (cSC)
- •cSC is a logical entity that may ride over overlay, virtual and physical entities that are provided by single or multiple operator (s)
 •Cloud Service can include application entities, cSC and associated resources, as well as just the application or just the connection
 •User interface can be L1, L1-L2, L1-L3, L1-L7
 •Service frames (packets) can be Ethernet, IP packet, MPLS packet, application PDU



Cloud Service Actors



Cloud Services





Architecture for Cloud Services by one Operator



Architecture for Cloud Services by Two Operator



Cloud Services Between Cloud Providers



Segments of cSC Crossing cC and cP



Cloud Services by Two cSPs



Interfaces













cSUI Attributes

- cSUI Id, Tenant ID
- NaaS Id
- Physical Interface: Ethernet, DOCSIS, EPON, GPON, WDM, SONET/SDH, OTN
- MTU
- Connection Multiplexing
- Protection
- Maximum Number of Connection Termination Points
- L2 Configuration Attributes [MEF10.3-MEF UNI], PPP, PPTP,
- L2 SOAM Attributes [MEF30.1 and 30.2]
- MPLS UNI Attributes [MPLS PVC User-to-Network Interface]
- IPv4 address, IPv6 address
- IP VPN
- L4 attributes
- L5 attributes
- L6 attributes
- L7 attributes
- Interface Level Security
- Service Level Security
- Operational State
- Administrative State



cSI Attributes

- cSI Id, VM ID
- List of NaaS Ids
- Interface Protection
- VM Protection
- MTU
- Connection Multiplexing
- Maximum Number of Connection Termination Points
- VM Portability
- L2 Configuration Attributes [MEF10.3-MEF UNI], PPP, PPTP,
- L2 SOAM Attributes [MEF30.1 and 30.2]
- MPLS UNI Attributes [MPLS PVC User-to-Network Interface]
- IPv4 address, IPv6 address
- IP VPN
- L4 attributes
- L5 attributes
- L6 attributes
- L7 attributes
- Interface Level Security
- Service Level Security
- Operational State
- Administrative State

Cloud Service Connection Termination Point (or End Point) (cSCTP)

Attributes Dynamic Attributes Traffic Management Fault Management Performance Management Protection Security

Cloud Service Connection (cSC)

Attributes Dynamic Attributes SLOs Fault Management Performance Management Protection Billing



Cloud Carrier-Provider Connection Termination Point (cSC-cp-TP)

Attributes Dynamic Attributes Traffic Management Fault Management Performance Management Protection Security

> Cloud Service Provider Connection (cSCcsp)

Attributes Dynamic Attributes SLOs Fault Management Performance Management Protection Billing



Cloud Services

- NaaS (MEF Services, Load Balancing, ELB, Domain Registration Service, Managed DNS, Network Appliances, IPv4/v6 Capable Dual Stack, Elastic IP Services, Overlay Network Services,...)
- IaaS (Storage Services, Databases, Disaster Recovery, Cloud Computing (Bare Metal Servers, High Performance Computing, Virtual Servers, ...))
- SECaaS (Managed access, NaaS security, Traffic Cleaning, etc.)
- PaaS (Managed application platform, scalable and high performing network, etc.)
- SaaS (On-demand Software Installation, Licensing, CDN, Email)
- CaaS (Virtual PBX, Voice and Video Conferencing, etc.)



Interconnectivity Services





NaaS Service Types

- EPL, EVPL, EP-LAN, EVP-LAN, EP-Tree, EVP-Tree, IP VPN, L2 VPN: On-demand with SLOs
- On-Demand Load Balancing: Local, global, or high availability LB
- Elastic Load Balancing
- Domain Registration Service
- Managed DNS
- Network Appliances (Firewalls, Routers, ...)
- IPv4 and IPv6 Capable Dual Stack
- Outbound Public Bandwidth
- Inbound Public Bandwidth
- Private Network Bandwidth
- Private and Public Port
- Elastic IP Addresses
- Overlay Network Services: PBB/PBT, L3VPN, VXLAN
- Security



NaaS Common Attributes

Cloud Services	
Network as a	Service Name
Service(NaaS)	Bandwidth
	Scheduled
	Shared
	Dedicated
	On-Demand
	Duration of Resource
	IPv4/IPv6 Address, VLAN and MAC
	Filtering
	NAT
	Firewall
	User Authentication
	Encryption
	Dynamic Scalability
	Billing



IaaS Common Attributes

Cloud Services			
Infrastructure (i.e.	Service Name		
IaaS)	CPU		
	Memory		
	Hard Disk Space		
	Dedicated		
	Shared		
	Scheduled		
	On-Demand		
	Duration of Resource		
	Operating Systems		
	User Authentication		
	Encryption		
	Data Security		
	Dynamic Scalability		
	NaaS attributes		
	Billing		



PaaS Common Attributes

Cloud Services			
Platform as a Service	Service Name		
(PaaS)	CPU		
	Memory		
	Hard Disk Space		
	Dedicated		
	Shared		
	Scheduled		
	On-Demand		
	Duration of Resource		
	Operating Systems		
	User Authentication		
	Encryption		
	Dynamic Scalability		
	Data Security		
	NaaS attributes		
	Billing		



SaaS, CaaS, and SECaaS Common Attributes

Cloud Services	
Software as as Service	Service Name
(SaaS)	Licensing
	On-demand Software Installation
	NaaaS Attributes
Communications as a	Service Name
Service (CaaS)	Number of users
	Licensed
	Unlicensed
	SLAs
	Service Type
	Data Security
	Authentication Realm
	NaaS attributes
	Billing
Security as a Service	Security Service Type
(SECaaS)	Security function
	Billing



OAM for Cloud Services

•Service Availability-

- Monthly Uptime of four 9s or five 9s
- Unavailable-No external connectivity, Zero read/write I/O, etc.
- •Provisioning-Rapid provisioning, resource changing, automated OS reload, remote reboot, etc.
- Performance Management-Periodic measurements, TCA, etc.
 Fault Management-Discovering and monitoring virtual resources, scheduled maintenance, upgrade events, etc.
 Billing-Fixed, Usage Based, etc.
- •Testing-Verification of attributes of each interface, connections, cloud services





CloudEthernet.org

ETSI NFV Bare Metal Server and VNF Interfaces





VM Interfaces



Mapping of OCC and NFV Interfaces

Architectural Construct	ETSI NFV Construct	OCC Construct
User Interface	(Vi-Ha)+(Vn-Nf)/VN	cSUI
VM Interface	(Vn-Nf)/VM	cSI
Container Interface	Container Interface	cSI
SWA-1	Software Architecture-1	cSI
Cloud Carrier-Cloud Provider		cCcPI
Interface		
Cloud Service Provider-Cloud		cSPcSPI
Service Provider Interface		
Connection between Users or	VNF Forwarding	cSC
between a User and VM or between	Graph	
VMs		
Connection Termination Point		cSCTP



NaaS with VNF Interfaces





NaaS with Bare Metal Server Interface





VM Interface





Virtualized cSC between Two cSUs



Virtualized Implementation





Virtualized cSC between cSUI and cSI



Virtualized Implementation





Virtualized cSC Crossing Two cSPs



SDN Architecture and Management





Cloud Services Management User **OSS/BSS** Portal Application Application Application Services **Cloud Orchestrator** North Bound API **NFV** Orchestrator Controller Controller Controller NMS/ **VNF** Manager South Bound API **EMS** Virtual Infrastructure Manager (Vn-NF)/VM cSC cSCTP₂ cSCTP₁ SWA-SWA-1 VNF /NF **VNF** loud Hypervi Virtual Network CCCPI **cSC** ervice VM SWA-5 Network HW Jser **cSUI** cSI SWA-5 SWA-5 Open Stac Vn-Nf)/VN +Vi-Ha

CloudEthernet.org

Cloud Services Management with Multiple Operators







CloudEthernet.org

OpenCloud Testbed





What is Next?

- Development of Implementation Agreements for Interfaces and Connections
- Development of Implementation Agreements for Services
- Development of Implementation Agreements for OAM and Service OAM
- Development of Testing and Certification Guidelines for Services
- Development of APIs and YANG Models
- Development of Life Cycle Service Orchestration for Cloud Services
- Collaborating with other SDOs for implementation, and API and YANG model development



Thank You!

